

MAGNETIC BASE DRILL

MANUAL

AO-5575A

ENHANCED PRODUCTIVITY AND SAFETY

FEATURES

- · Manual feed
- · For smooth cutting of deep and large holes
- A real work horse
- New powerful single speed motor 520rpm
- · 1020 kg/f double rectangular magnet
- · Cuts up to 55mmø thru 75mm plate
- · One-touch arbor
- · Supplied in sturdy carry case

ADVANCED SAFETY SYSTEM

Fresh compact design that answers the customer's needs

From the extremely efficient electro-magnet to the reversible feed handles, the AO-5575A ATRA adapts to more user needs while offering safety where its peeded most. Original Hibrarch cutters

where its needed most. Original Hibroach cutters drastically shorten drilling time when compared to similar sized conventional twist drills. Optional chuck allows the use of up to 13mm twist drills to be inserted.

Built-in motion sensor

If any lateral movement or excess vibrations detected, the drill stops instantly. Nitto Kohki are the first company to incorporate this feature into magnetic base drills.

Over-load Shutdown

When excessive load is detected during the drilling process, the drill motor will automatically shutdown protecting itself from damage. Once overloaded, the motor 'Start' switch is required to be depressed to resume drilling.

Fail-safe Restart

In the event of a power loss while drilling, the drill will not restart even after power is resupplied. The motor 'Start' switch is required to be depressed to resume drilling.

Magnet Open-Circuit Sensor

The drill will not start if the magnet fails to energize due to an open field or faulty wire.

ANNULAR CUTTERS

Broach cutters are far more efficient than twist drills

Nitto Kohki Atra Ace magnetic drills combined with **HIBROACH** and **JETBROACH** annular cutters provide faster, cost-effective cutting and better hole finishes than conventional twist drills.




DIMENSIONS	AO-5575A Unit : mm
(upper limit) (upper limit) (lower limit) 136	889 170 37 296

Model No.	Power Source	Rated Power Consumption	No Load Speed	Hole Diameter	Plate Thickness	Magnet Holding Power	Weight
AO-5575A	220~240V AC 50/60HZ	950W	520rpm	12 - 55mm	9 - 75mm	1,020 kg/f	17.5kg

ATRACE

MAGNETIC BASE DRILL

LED load detector with 'Smart-Stop / Rapid-Restart' Technology



Built-In Coolant Tank

Possible damage to the coolant tank is prevented with this built-in coolant tank feature.

